

FX-1502



PRODUCT DESCRIPTION:

The Foxcroft FX-1502 series of toxic gas leak detectors are perfect for monitoring two different gases or two gas container storage, generation or use areas, simultaneously. The remote display unit can be located in a control room or safe area up to 2,000 feet away from the potential gas leak.

Includes silence & reset buttons. Each channel includes: (2) Alarm levels, (1) Digital display in ppm or % Oxygen, (3) LED alarm indicators, (2) Relay contacts.

Optional 4-20mA retransmission output scalable to the sensor operating range is available for connection to SCADA, data loggers, or chart recorders. Special alarm levels and ranges are available on written request. An optional battery backup/surge protector is recommended for applications where AC power is unreliable, or must be maintained in the event of a power failure.

Specifications

Sensor Input:	Two gas sensors
Sensor Distance From Display:	25 feet standard cable length, 2000 feet maximum each channel
Measuring Principle:	3-Electrode, electrochemical fuel cell
Response Time (T₉₀):	<60 Seconds at 20°C. Typically less than 8 seconds to full alarm
Long-term Sensitivity Drift:	Less than 2% signal loss per month
Temperature Range:	-20°C to +50°C (-4°F to 122°F)
Humidity Range:	15 - 90 % (non-condensing)
Accuracy:	0.1 PPM (@20 degree C)
Resolution:	0.1 PPM
Dimensions, Remote Display :	7" high x 7" wide x 5" deep (approx. w/ mounting ears)
Dimensions, Sensor:	4" high x 4" wide x 2.5" deep (on 7" x 7" x 1/4" mounting plate)
Sensor Expected Operating Life:	2 years in air, Oxygen 2 years in air
Power Supply:	110/ 220 VAC, 50/60 Hz
4-20 mA Output (optional):	(2) Analog 4-20mA output @ 300 ohms maximum, scalable to sensor operating range
Auxiliary Relay (Danger Alarm):	SPDT 10A @ 125 (latching) each channel
Configurable Relays:	Secondary relay - SPST 10A @ 125VAC Warning, Danger , Danger non-latching each channel
Audible Alarm	Integral Piezo Buzzer, 100 dB
Alarm Levels:	(2) Alarm levels per channel, Warning & Danger
Instrument & Sensor Mounting:	NEMA 4X Wall mount
Warranty:	Electronics 1 year, toxic gas sensor 1 year
Gas Sensors Available:	Ammonia, Carbon Monoxide, Chlorine, Chlorine Dioxide, Hydrogen, Hydrogen Chloride, Hydrogen Cyanide, Hydrogen Sulfide, Nitrogen Dioxide, Nitric Oxide, Oxygen, Ozone, Sulfur Dioxide
(Sensor specifications based on Chlorine)	Manufactured completely in Glenmoore, PA except gas sensors made in Europe

www.chemtech-us.com

Westtown Business Center 1568 McDaniel Drive West Chester, PA 19380 USA
P: 610-566-7177 F: 484-266-7137

sales@chemtech-usa.com Follow us on LinkedIn: Chemtech International Inc